

100 Valley Street Lee, MA 01238 1-413-637-1060 (Office) 1-413-637-1164 (Fax)

Laver 1

PRODUCT SPECIFICATION SHEET

Product: Assault Glass

MAKEUP:
Layer 1: 1/8" Heat Stregthened Glass

Layer 2: .03 PVB

Layer 3: 1/8" Heat Stregthened Glass ATTACK
Layer 4: .03 PVB SIDE


Layer 5: 1/8" Heat Stregthened Glass

Layer 6: .03 PVB

Layer 7: 1/8" Heat Stregthened Glass

Layer 8: .03 PVB

Layer 9: 1/8" Heat Stregthened Glass



ATTACK SIDE

Layer 9

OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent

White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low E

Many more to choose from (please inquire)

Size and Thickness may not be available for every option

Thickness Average			Dimensional Tolerance
.75"	9	74%	ASTM C 1349

STANDARDS: ANSI Z97.1-1984 Safety Glazing Materials for Buildings.

ASTM C 1036 Standard Specification for Flat Glass.

ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

BALLISTIC AND FORCED ENTRY RATINGS

Proprietary Information not for Public Distribution