




100 Valley Street Lee, MA 01238
 1-413-637-1060 (Office)
 1-413-637-1164 (Fax)

PRODUCT SPECIFICATION SHEET

Product: **GCP 375 3/8"**

MAKEUP:

- Layer 1: **1/8" Heat Strengthened Glass**
- Layer 2: **.05 Urethane**
- Layer 3: **1/16" Polycarbonate**
- Layer 4: **.05 Urethane**
- Layer 5: **1/8" Heat Strengthened Glass**



OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent
 White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low E
 Many more to choose from (please inquire)
 Size and Thickness may not be available for every option

| Thickness Average | Weight Lbs | Light Transmissior | Dimensional Tolerance |
|-------------------|------------|--------------------|-----------------------|
| 0.375 | 4 | 86% | ASTM C 1349 |

STANDARDS: **ANSI Z97.1-1984 Safety Glazing Materials for Buildings.**
ASTM C 1036 Standard Specification for Flat Glass.
ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

BALLISTIC AND FORCED ENTRY RATINGS

H.P. White TP-0500.02 Level I – Forced Entry