



100 Valley Street Lee, MA 01238
 1-413-637-1060 (Office)
 1-413-637-1164 (Fax)


PRODUCT SPECIFICATION SHEET

Product: **GCP 530 1/2"**

MAKEUP:

- Layer 1: **1/8" Heat Strengthened Glass**
- Layer 2: **.05 Urethane**
- Layer 3: **3/16" Polycarbonate**
- Layer 4: **.05 Urethane**
- Layer 5: **1/8" Heat Strengthened Glass**

**ATTACK
SIDE**



- OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent
 White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low E
 Many more to choose from (please inquire)
 Size and Thickness may not be available for every option

Thickness Average	Weight Lbs	Light Transmissior	Dimensional Tolerance
0.53	4.79	86%	ASTM C 1349

- STANDARDS: **ANSI Z97.1-1984 Safety Glazing Materials for Buildings.**
ASTM C 1036 Standard Specification for Flat Glass.
ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

BALLISTIC AND FORCED ENTRY RATINGS

- H.P. White TP-0500.02 Level I – Forced Entry
- H.P. White Level A Ballistics – 38 Special (Low Spall)