

100 Valley Street Lee, MA 01238 1-413-637-1060 (Office) 1-413-637-1164 (Fax)

PRODUCT SPECIFICATION SHEET

Product: **PAS 002 AG 1 3/8"**

MAKEUP:

Layer 1: 3/8" Glass
Layer 2: .03 PVB
Layer 3: 3/8" Glass
Layer 4: .03 PVB
Layer 5: 3/8" Glass
Layer 6: .03 PVB
Layer 7: 3/16" Glass

ATTACK SIDE Layer 1 Layer 7

OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent

White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low E

Many more to choose from (please inquire)

Size and Thickness may not be available for every option

Thickness		Light	Dimensional
Average		Transmission	Tolerance
1.4	17.94	70%	ASTM C 1349

STANDARDS: ANSI Z97.1-1984 Safety Glazing Materials for Buildings.

ASTM C 1036 Standard Specification for Flat Glass.

ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

BALLISTIC AND FORCED ENTRY RATINGS

U.L. 752 Level II – 357 mag

Proprietary Information not for Public Distribution