

100 Valley Street Lee, MA 01238 1-413-637-1060 (Office) 1-413-637-1164 (Fax)

PRODUCT SPECIFICATION SHEET

Product: **PAS 003 AG 1 9/16**"

MAKEUP:

 Layer 1:
 3/8" Glass

 Layer 2:
 .03 PVB


 Layer 3:
 3/8" Glass

 Layer 4:
 .03 PVB

 Layer 5:
 3/8" Glass

 Layer 6:
 .03 PVB

 Layer 7:
 3/8" Glass





OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low E Many more to choose from (please inquire)

Size and Thickness may not be available for every option

Thickness	Weight	Light	
Average	Lbs	Transmission	
1.59	20.38	68%	ASTM C 1349

STANDARDS: ANSI Z97.1-1984 Safety Glazing Materials for Buildings. ASTM C 1036 Standard Specification for Flat Glass. ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

BALLISTIC AND FORCED ENTRY RATINGS

U.L. 752 Level III – 44 mag

Proprietary Information not for Public Distribution