

100 Valley Street Lee, MA 01238 1-413-637-1060 (Office) 1-413-637-1164 (Fax)

PRODUCT SPECIFICATION SHEET

Product: PAS 004 AG 2" Layer 9 Layer 1 MAKEUP: Layer 1: 3/8" Glass Layer 2: .03 PVB Layer 3: 3/8" Glass **ATTACK** SAFE Layer 4: .03 PVB SIDE SIDE Layer 5: 3/8" Glass Layer 6: .03 PVB Layer 7: **3/8" Glass** Layer 8: .03 PVB Layer 9: 3/8" Glass

OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent

White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low E

Many more to choose from (please inquire)

Size and Thickness may not be available for every option

Thickness		Light	Dimensional
Average		Transmission	Tolerance
2	25.63	64%	ASTM C 1349

 ${\tt STANDARDS:} \ \ \textbf{ANSI Z97.1-1984 Safety Glazing Materials for Buildings.}$

ASTM C 1036 Standard Specification for Flat Glass.

ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

BALLISTIC AND FORCED ENTRY RATINGS

U.L. 752 Listed Level 4 – .30 Caliber Rifle

Proprietary Information not for Public Distribution