

100 Valley Street Lee, MA 01238 1-413-637-1060 (Office) 1-413-637-1164 (Fax)

ATTACK

SIDE

Layer 1

Layer 9

SAFE

SIDE

PRODUCT SPECIFICATION SHEET

Product: **PAS 007** 1/ 7/8"

MAKEUP:

Layer 1: 3/8" Glass

Layer 2: .025 Urethane

Layer 3: 3/8" Glass

Layer 4: .025 Urethane

Layer 5: 3/8" Glass

Layer 6: .025 Urethane

Layer 7: 3/8" Glass

Layer 8: .05 Uirethane

Layer 9: 1/4" Mar Resistant Polycarbonate

OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent

White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low ${\tt E}$

Many more to choose from (please inquire)

Size and Thickness may not be available for every option

Thickness	Weight	Light	Dimensional
Average	Lbs	Transmission	Tolerance
1.827	21.32	67%	ASTM C 1349

 ${\tt STANDARDS:} \ \ \textbf{ANSI Z97.1-1984 Safety Glazing Materials for Buildings.}$

ASTM C 1036 Standard Specification for Flat Glass.

ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

BALLISTIC AND FORCED ENTRY RATINGS

UL-752 Level 7

Proprietary Information not for Public Distribution