




100 Valley Street Lee, MA 01238
 1-413-637-1060 (Office)
 1-413-637-1164 (Fax)

PRODUCT SPECIFICATION SHEET

Product: **PAS 008 AG 2 7/16"**

MAKEUP:

- Layer 1: **3/8" Glass**
- Layer 2: **.03 PVB**
- Layer 3: **3/8" Glass**
- Layer 4: **.03 PVB**
- Layer 5: **3/8" Glass**
- Layer 6: **.03 PVB**
- Layer 7: **3/8" Glass**
- Layer 8: **.03 PVB**
- Layer 9: **3/8" Glass**
- Layer 10: **.03 PVB**
- Layer 11: **3/8" Glass**



OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low E
 Many more to choose from (please inquire)
 Size and Thickness may not be available for every option

Thickness Average	Weight Lbs	Light Transmissior	Dimensional Tolerance
2.4	29.76	60%	ASTM C 1349

STANDARDS: **ANSI Z97.1-1984 Safety Glazing Materials for Buildings.**
ASTM C 1036 Standard Specification for Flat Glass.
ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

BALLISTIC AND FORCED ENTRY RATINGS

H.P. White - 7.62 AP