




100 Valley Street Lee, MA 01238
 1-413-637-1060 (Office)
 1-413-637-1164 (Fax)

PRODUCT SPECIFICATION SHEET

Product: **PAS 5000 1 5/8"**

MAKEUP:

- Layer 1: **1/4" Glass**
- Layer 2: **.05 Urethane**
- Layer 3: **1/2" Glass**
- Layer 4: **.05 Urethane**
- Layer 5: **1/2" Glass**
- Layer 6: **.05 Urethane**
- Layer 7: **1/8" Polycarbonate**
- Layer 8: **.025 Urethane**
- Layer 9: **1/8" Mar Resistant Polycarbonate**



OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent
 White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low E
 Many more to choose from (please inquire)
 Size and Thickness may not be available for every option

Thickness Average	Weight Lbs	Light Transmission	Dimensional Tolerance
1.64	19.3	68%	ASTM C 1349

STANDARDS: **ANSI Z97.1-1984 Safety Glazing Materials for Buildings.**
ASTM C 1036 Standard Specification for Flat Glass.
ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

BALLISTIC AND FORCED ENTRY RATINGS

NIJ Level III - B-6 7.62 NATO Level B6

Proprietary Information not for Public Distribution