

100 Valley Street Lee, MA 01238 1-413-637-1060 (Office) 1-413-637-1164 (Fax)

## PRODUCT SPECIFICATION SHEET

Product: PAS UL-1 Layer 1 Layer 9 MAKEUP: Layer 1: 3/16" Glass Layer 2: .015 PVB Layer 3: **3/16" Glass** ATTACK SAFE SIDE Layer 4: .015 PVB SIDE Layer 5: 3/8" Glass Layer 6: .015 PVB Layer 7: **3/8" Glass** Layer 8: .015 PVB Layer 9: 1/8" Glass

OPTIONS: Tinted Glass (Gray, Bronze, Green, Blue); Reflective Glass; One-way Mirror; Translucent

White Interlayer (Frosted Glass); Wire Glass; Insulating Units; Low E

Many more to choose from (please inquire)

Size and Thickness may not be available for every option

Thickness		Light	Dimensional
Average		Transmission	Tolerance
1.28	16.2	73%	ASTM C 1349

STANDARDS: ANSI Z97.1-1984 Safety Glazing Materials for Buildings.

**ASTM C 1036 Standard Specification for Flat Glass.** 

**ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass** 

## **BALLISTIC AND FORCED ENTRY RATINGS**

U.L. 752 Listed Level 1 – 9mm

Proprietary Information not for Public Distribution